

DOSING PUMP FOR LIQUIDS

SIMDOS 02



Hydraulic data

Flow rate	Dosing volume	Suction height	Max. pressure
30 μl/min–20 ml/min	30 μl–999 ml	2 mWg	6 bar

Chemical resistance

Code	Pump head	Diaphragm	Valves	Filter ¹⁾
KT	PP	PTFE covered	FFKM Kalrez [®]	PEEK
TT	PVDF	PTFE covered	FFKM Kalrez [®]	PVDF
FT	PTFE	PTFE covered	FFKM Kalrez [®] *	PEEK
ST	STAINLESS STEEL	PTFE covered	FFKM Kalrez [®] *	PEEK

*On request FFKM Chemraz ® material for housing and filter mesh

Functions

S Version	RC Version		RC Plus Version
Manual operation	 Manual operation Analog control: 0–5 V, 0–10 V, 0–20 mA, 4–20 mA, from 1 to 100% Start/Stop through logic control (TTL) 	 Reset/Prime through logic control (TTL) Output signal fault alarm Cable for external control included 	Same as RCPlus RS 232

Technical data

- Main supply 100–240 V / 50–60 Hz
- Ambient temperature allowed +5 to +40 °C
- Liquid temperature allowed +5 to +80 °C
- Maximum viscosity allowed 150 cSt
- Accuracy +/-2% (nominal value)
- Repeatability +/-1%

- Power consumption 10 W
- Protection class IP65
- Dimensions: 150 x 93 x 144
- Weight: 0.9 kg
- Hydraulic connection UNF 1/4"-28

ACCESSORIES

Valves kit

	ID-Nr.
Chemraz [®] special valves for certain chemicals	164984



Diaphragm pressure control valve with support when the feeding tank is above the pump

	ID-Nr.
Kit JFDV 30 KTZ	166286
Kit JFDV 30TTZ	166287
Kit JFDV 30 FTZ	166288



Filter

Тур	Material ¹⁾	Connector	ID-Nr.
FS 60 T	PVDF	UNF 1/4"-28	165210
FS 60 X	PEEK	UNF 1/4"-28	165212



1) material for housing and filter mesh

Connection tube

	ID-Nr.
Tube 1/16" with connector UNF 1/4"-28, 1 m for fine dosing	166335



Mounting plate

	ID-Nr.
for wall mounting	160473



Standfitting

	ID-Nr.
for retort stand	160474



Footswitch

	ID-Nr.
for impulse start and stop	155872

